
Product Information

Gaskamine 240

--- 1,3-benzenedimethanamine,

reaction products with styrene ---



MITSUBISHI GAS CHEMICAL COMPANY, INC.

Description Gaskamine 240 is a clear yellow liquid.

Typical Properties	Appearance, visual	color liquid
	Color, Gardner	1-2
	Flash Point, °C	205
	Amine value, mgKOH/g	403
	Specific gravity, 20°C	1.049
	Theoretical Active Hydrogen Equivalent Weight	103
	Viscosity, mPa·s, 25°C	66
	Solubility	Soluble in methanol, xylene, toluene, acetone Insoluble in water

Sales Specifications	Appearance, Visual	Color liquid
	Color, Gardner	<3
	Viscosity, mPa·s, 25°C	50-85
	Total Amine Value	390-415
	Moisture, %	<0.2

Applications Epoxy curing agent

Container Information Available in 200kg steel drums and 18kg cans.

Precautions for Safe Handling and Use**Extinguishing media**

Dry chemical, Regular foam, Water fog

Health safety precautions

Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Wash thoroughly the face, the hands after handling.

Storage conditions

Store in cool and dry place with adequate ventilation

For specific safety, handling and toxicity information, please refer to the current Material Safety Data Sheet.

First Aid**If inhaled**

Remove to fresh air immediately. Call a physician.

Skin contact

Wash exposed area thoroughly with plenty of soap and water while removing contaminated clothing and shoes. Call a physician.

Eye contact

Immediately flush eyes with plenty of water enough. Call a physician.

If swallowed

Immediately give 2 large glasses of water if victim is conscious. Call a physician. Never give anything by mouth to an unconscious person.

Chemical Registration Numbers

CAS: 404362-22-7

ELINCS: 445-790-1

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Mitsubishi Gas Chemical Company. It is the responsibility of the users to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patents.

**MITSUBISHI GAS CHEMICAL COMPANY, INC.**

Americas 520 Madison Avenue, 17th floor, New York, NY 10022 ♦ Phone: +1-212-752-4620 ♦ Fax: +1-212-758-4012
Europe Immermannstrasse 43, 40210, Dusseldorf, Germany ♦ Phone: +49-211-363088 ♦ Fax: +49-211-354457
Head Office 5-2, 2-chome, Marunouchi, Chiyoda-ku, Tokyo 100-8324 Japan ♦ Phone: +81-3-3283-4812 ♦ Fax: +81-3-3214-0938