
Product Information


OTA
--- O-TOLUIC ACID ---



MITSUBISHI GAS CHEMICAL COMPANY, INC.

Description

o-TOLUIC ACID
Chemical formula: o-CH₃C₆H₄COOH



Molecular weight: 136

Typical Properties

Appearance, visual	Solid , Clear
Purity, wt%	99
Melting Point, °C	103.7
Boiling Point, °C	258~260
Specific gravity, 15°C solid	1.073
Vapor Pressure, 157°C, mmHg	24

Sales Specifications

Purity, wt%	min 99.0
-------------------	----------

Applications

Container Information

435kgs flexible container
25kgs paper bag

Precautions for Safe Handling and Use

Extinguishing media

Small fire: Carbon dioxide,
Large fire: Water spray

Health safety precautions

Avoid contact with eyes, skin and clothing.
Avoid breathing vapor.
Wash thoroughly the face, the hands after handling.

Storage conditions

Store in cool and dry place.

For specific safety, handling and toxicity information,
please refer to the current Material Safety Data Sheet.

First Aid

If inhaled

Remove to fresh air immediately. Call a physician.

Skin contact

Wash skin thoroughly with a plenty of soap and water
while removing contaminated clothing and shoed.

Eye contact

Immediately flush eyes with a plenty of water enough.
Call a physician.

If swallowed

Induce vomiting if victim is conscious. Call a physician.
Never give anything by mouth to an unconscious person.

Chemical Registration Numbers

CAS: 118-90-1
EINECS: 204-284-9

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Mitsubishi Gas Chemical Company. It is the responsibility of the users to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patents.



MITSUBISHI GAS CHEMICAL COMPANY, INC.

Americas 520 Madison Avenue, 17th floor, New York, NY 10022 ◆ Phone: +1-212-752-4620 ◆ Fax: +1-212-758-4012
Europe Immermannstrasse 43, 40210, Dusseldorf, Germany ◆ Phone: +49-211-363088 ◆ Fax: +49-211-354457
Head Office 5-2, 2-chome, Marunouchi, Chiyoda-ku, Tokyo 100-8324 Japan ◆ Phone: +81-3-3283-4812 ◆ Fax: +81-3-3214-0938